## Summary of Replies for AMS6458J

Print

| Name | Committee | Comment Type | Section/Paragraph |
|---|---|---|---|
| Shlomo Ramati | AMSE | I | 0.0 |

APPROVE

| | | | |
|---|---|---|---|
| Anatoly Neyman | AMSE | T | 1.3, 3, 4, and 8.5 |

Remove from the specification paragraph ***"1.3 Classification"*** entirely: the only type of wire that will be produced per this Specification shall be ***"Bare Wire"***. Accordingly additional editorial changes in the above respect shall be made by ***deleting paragraph 3.4.6***.

Remove any requirements for Tensile Tetsing per ***paragraphs 3.5.3., 4.3., and 4.5***.

In paragraph 3.4.4. add after "...***Butt welding is perfmissible - ONLY AT DIAMETERS LARGER (BIGGER) THAN FINAL..."***

In paragrah 3.7.2. add after "...***or 914mm) length, OR OTHER LENGTHS SPECIFIED BY PURCHASER...***"

In paragraph 4.1. after "*The vendor*" delete "***of wire shall supply all samples for vendor's tests and***" leaving "*shall be responsible for the performance of all required tests.*"

In paragraph 4.2.2. remove "*..., and tensile properties (3.5.3)...*"

In paragraph 8.5. add after "***and hydrogen content, AND DEVELOPING OXIDES AND RUST ON SURFACE OF WIRE"***.

Since paragraph 4.3. is to be removed completely change numerical sequence of the following paragraphs 4.4 to 4.3.

| | | | |
|---|---|---|---|
| Ronald Hahn | AMSE | I | 3.6.5 |

This is a Bob Hodder comment that is being transfered from the "do not use" duplicate ballot.

Refer to 3.4.5 of the AMS6457D draft. It has a lengthy phrase at the end that maybe should be part of this spec as well.

| | | | |
|---|---|---|---|
| Robert Steffen | AMSE | I | 4.2.2 |

For clarity - After "nitrogen", insert "on finished wire".