Summary of Replies for AMS6457D

Print

Name	Committee	Comment Type	Section/Paragraph
Anatoly Neyman	AMSE	T	1.3, 3, 4, and 8.5

Remove from the specification paragraph ***"1.3 Classification"*** entirely: the only type of wire that will be produced per this Specification shall be ***"Bare Wire"***. Accordingly additional editorial changes in the above respect shall be made by ***deleting paragraph 3.4.6***.

Remove any requirements for Tensile Tetsing per ***paragraphs 3.5.3., 4.3., and 4.5***.

In paragraph 3.4.4. add after "...***Butt welding is perfmissible - ONLY AT DIAMETERS LARGER (BIGGER) THAN FINAL..."***

In paragrah 3.7.2. add after "...***or 914mm) length, OR OTHER LENGTHS SPECIFIED BY PURCHASER...***"

In paragraph 4.1. after "*The vendor*" delete "***of wire shall supply all samples for vendor's tests and***" leaving "*shall be responsible for the performance of all required tests.*"

In paragraph 4.2.2. remove "*..., and tensile properties (3.5.3)...*"

In paragraph 8.5. add after "***and hydrogen content, AND DEVELOPING OXIDES AND RUST ON SURFACE OF WIRE"***.

Since paragraph 4.3. is to be removed completely change numerical sequence of the following paragraphs 4.4 to 4.3.

Robert Steffen	AMSE	I	4.2.2

For clarity - After "nitrogen", insert "on finished wire".