

List of Chapters

Chapter 1 Belt Separation

- 1.1 Belt-to-Belt Separation (or Belt Separation)—Discussion
- 1.2 Belt Separation—Crack Initiation and Propagation
- 1.3 Root Causes of and Contributors to Belt Separation
 - 1.3.1 Over-Deflection
 - 1.3.2 High Speed
 - 1.3.3 High Ambient and Pavement Temperatures
 - 1.3.4 Road Hazards (Impacts)
 - 1.3.5 Ozone Deterioration
 - 1.3.6 Physiological Damage
 - 1.3.7 Unrepaired or Improperly Repaired Punctures
 - 1.3.8 Improper Tire Maintenance
 - 1.3.9 Vehicle-Related Conditions
 - 1.3.10 Mounting and/or Demounting Damage
 - 1.3.11 Poor Storage of Tires
 - 1.3.12 Cuts, Snags, Gouges, Tears, and Abrasions
 - 1.3.13 Penetrations
 - 1.3.14 Manufacturing and Design Conditions

Chapter 2 Belt Separation Identification

- 2.1 Tread and Belt Are Detached
 - 2.1.1 Belt Detachment Characteristics
 - 2.1.2 Belt Stock Degradation
 - 2.1.3 Road Rash
- 2.2 Intact Top Belt and Tread
- 2.3 Accelerated Wear—Underlying Separation
- 2.4 Belt Separation—Additional Notes

Chapter 3 Other Types of Belt Separation

- 3.1 Belt Edge Separation
- 3.2 Incipient Belt Edge Separation
- 3.3 Atypical Belt Separation

Chapter 4 Identification of Causes and Contributors to Belt Separation

- 4.1 Punctures
 - 4.1.1 Over-Deflection
 - 4.1.2 Intra-Carcass Pressurization
 - 4.1.3 Water and Salt Corrosion
 - 4.1.4 Breakage of Belt Wires
- 4.2 Over-Deflection
 - 4.2.1 Observation of the Compression Groove
 - 4.2.2 Wrinkling of the Innerliner
 - 4.2.3 Innerliner Color or Discoloration
 - 4.2.4 Exterior Sidewall Contact with the Road Surface
 - 4.2.5 Observation of the Tread Shoulders
 - 4.2.6 Wheel Weight Clip Mark Depth
 - 4.2.7 Shifting or Chattering of the Balance Weight Mark

- 4.2.8 Interior (Liner Side) of the Bead Toe—Creased or Cracked
- 4.2.9 Bead Face Abrasion or a Circumferential Line in the Bead Face
- 4.2.10 Creasing of the Base Radii of the Tread Grooves
 - 4.3 Penetrations
 - 4.3.1 Tread Attached to the Casing
 - 4.3.2 Tread and Top Belt Detached
 - 4.4 Impacts
 - 4.4.1 Identification of Road Hazard Impacts
 - 4.4.2 Identification of Belt Separation Due to Impact
 - 4.5 Ozone Deterioration
 - 4.6 Mounting and/or Demounting Damage
 - 4.7 Physiological Aging
 - 4.7.1 Durometer
 - 4.7.2 Appearance and Feel
 - 4.7.3 Spot Ozone Damage
 - 4.7.4 Belt Tearing
 - 4.8 Snags, Gouges, Cuts, Tears, and Abrasions
 - 4.9 Cutting and Chipping
 - 4.10 Poor Tire Storage and Improper Tire Maintenance
 - 4.11 High Speed and High Ambient and/or Pavement Temperatures
 - 4.12 Vehicle-Related Conditions

Chapter 5 Identification of Non-Belt Separations

- 5.1 Tread Separation
- 5.2 Bead Area Separation
 - 5.2.1 Lower Sidewall Compound Separation Off the Plies
 - 5.2.2 Separation Between the Ply Turn-Up(s) or Turn-Down(s)
 - 5.2.3 Separation of the Bead Wires or Bundle from the Surrounding Plies
 - 5.2.4 Separation Between the Steel or Fabric Chipper or Chafer
 - 5.2.5 Bead Breaks
- 5.3 Sidewall Separation
 - 5.3.1 Separation Between the Plies
 - 5.3.2 Separation Between the Sidewall Compound Components
 - 5.3.3 Separation Between the Ply and the Sidewall Compound

Chapter 6 Identification of Various Tire Conditions

- 6.1 Run-Flat Damage
- 6.2 Chemical Damage to the Tread and Sidewall
- 6.3 Non-Ozone-Related Cracking, Indentations, and Bulges
- 6.4 Identification of Innerliner Conditions

- 6.4.1 Appearance of a Lap Splice
- 6.4.2 Appearance of a Butt Splice
- 6.4.3 Liner Tags
- 6.4.4 Liner Openings
- 6.4.5 Ply Cord Shadowing in the Liner

Chapter 7 Identification and Significance of Balance Weight Marks

- ### Chapter 8 Location of the Tire on a Vehicle
- 8.1 Outboard Side Versus Inboard Side
 - 8.2 Rear Position Versus Front Position
 - 8.3 Left Side Versus Right Side of the Vehicle

Chapter 9 Addressing Several Failure Theories

- 9.1 Brassy Wire Failure
 - 9.1.1 No Bonding Between the Brass Laminate and the Belt Compound
 - 9.1.2 Partial Bonding Between the Brass Laminate and the Belt Compound
 - 9.1.3 Proper Bonding and Brassy Wire Appearance
- 9.2 Manufacturing Imprints—"Liner Marks"
- 9.3 Nylon Overlay

Chapter 10 Visual and Tactile Nondestructive Tire Investigation Techniques

- 10.1 Basic Inspection Process
- 10.2 Marking the Tire for Inspection
- 10.3 Examination Process—Notes and Photographs
 - 10.4 Tactile and Visual Inspection of the Tire
 - 10.4.1 Serial Side Sidewall
 - 10.4.2 Beads
 - 10.4.3 Opposite Serial Side Sidewall
 - 10.4.4 Tread
 - 10.4.5 Belts
 - 10.5 Inspection Procedure—Demounting a Tire from the Wheel
 - 10.6 Wheel Inspection
 - 10.7 Matching the Wheel to the Tire
 - 10.8.1 Identifying Multiple Past Tire Balances
 - 10.9 Photography

Appendix A: References

Appendix B: Terms

Appendix C: Compression Groove

Appendix D: Run-Flat Sequence

Appendix E: Shell Rating Scale for Ozone Deterioration